

AVISTA pace EVO FE SAE 0W-30

Ultra-modern and extremely economical passenger car engine oil (petrol, diesel) from the AVISTA pace EVO line for vehicles with modern exhaust gas aftertreatment and long-life service interval to meet the prescribed OEM approvals.

APPLICATION

- passenger cars, light commercial vehicles, petrol, diesel, with modern exhaust aftertreatment

CHARACTERISTICS / APPLICATION BENEFITS

- Mid SAPS
- extremely fuel-efficient
- low evaporation loss
- resistance to ageing
- viscosity stability
- low exhaust emissions
- low wear
- cleanliness of the engine
- extended maintenance interval

APPROVALS

Volkswagen 504 00 / 507 00

SPECIFICATIONS

ACEA C3
BMW LL 04
MB-Approval 229.52
 229.51
 229.31
Porsche C30

RECOMMENDATIONS

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		0W-30
Density 15 °C	DIN EN ISO 12185	g/cm ³	0.820 – 0.860
Kin. Viscosity @ 100 °C	DIN 51562-1	mm ² /s	11.2 – 12.5
Viscosity Index	DIN ISO 2909		190
Total Base Number	DIN ISO 3771	mg KOH/g	7.5 – 9.5
Dyn. Viscosity @ -30 °C	DIN 51377	mPa*s	max. 6.200
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	DIN ISO 3016	°C	max. -48

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 1)